

TAU

Revestimiento Wall tile Faltence Riv Domme Silver 30,3x60,5 y et Riv Domme Pearl 30,3x60,5.



Domme Pearl 30,3x60,5 cm. M 8



Domme Silver 30,3x60,5 cm. M 8



RLV Domme Pearl 30,3x60,5 cm. M 9



RLV Domme Silver 30,3x60,5 cm. M 9

DOMME

MATE MATT MATE

W

V2

Nr O

FORMATOS SIZES FORMATS



30,3x60,5 12"x24"

PIEZAS ESPECIALES SPECIAL PIECES PIÈCES SPÉCIALES



Belay Silver 7x60,5 cm. P 12

Peril Plata Mate 1 x 60,5 cm. P 10

PAVIMENTO SUGERIDO
RECOMMENDED FLOOR SOL CONSEILLÉ

P VERMAND 60x60 (page 16)



Pearl

Silver

ESPECIFICACIONES TÉCNICAS
TECHNICAL SPECIFICATIONS SPÉCIFICATIONS TECHNIQUES



CUMPLE



18 %



20 / 30



RESISTE



RESISTE



GA



CUMPLE





Revestimiento Wall tile Palencia Wall tile Domme Silver 30,3x60,5, Domme Pearl 30,3x60,5 y and of Bailey Silver 7x60,5. Pavimento Floor tile Sol Vermand Silver 60x60.

TAU

Revestimiento Wall tile Balance: Domme White 30,3x60,5, Domme Tan 30,3x60,5 y el Beige Tan 7x60,5. Pavimento Floor tile Sol Vermand Beige 60x60.



Domme White 30,3x60,5 cm. M 8



Domme Tan 30,3x60,5 cm. M 8



RLV Domme White 30x60,5 cm. M 9



RLV Domme Tan 30x60,5 cm. M 9

DOMME

MATE MATT MATE

W

V2

Nr O

FORMATOS SIZES FORMATS



DESIGNS 10
30,3x60,5 12"x24"

PIEZAS ESPECIALES SPECIAL PIECES PIÈCES SPÉCIALES



Beige Tan 7x60,5 cm. P 12



Perfil Oro Mate 1 x 60,5 cm. P 11

PAVIMENTO SUGERIDO
RECOMMENDED FLOOR SOL CONSEILLÉ

P VERMAND 60x60 (page 18)



Beige

ESPECIFICACIONES TÉCNICAS
TECHNICAL SPECIFICATIONS SPÉCIFICATIONS TECHNIQUES



CUMPLE



18 %



20 / 30



RESISTE



RESISTE



GA



CUMPLE

